

Orlock Stainless Steel

Protruding Head

Before Installation


After Installation

Body Material: Austenitic Stainless Steel - AISI 304 Cu

Body Finish: Natural

Mandrel Material: Austenitic Stainless Steel - AISI 304 Cu

Mandrel Finish: Natural



Dimensions - Nominal (millimeter)

Forces - Nominal (Kgf)

		ART.No		MIN	MAX						
4.8	4.9-5.1	LN48090P	9.0	1.5	3.5				620		5,000
		LN48115P	11.5	3.5	6.0						4,000
		LN48140P	14.0	6.0	8.5	2.2	9.8	3.0	700	510	3,000
		* LN48165P	16.5	8.5	11.0						3,000
		* LN48190P	19.0	11.0	13.0						3,000
6.4	6.6-6.7	LN64105P	10.5	2.0	4.5				1440		2,000
		LN64125P	12.5	4.0	6.5						2,000
		LN64145P	14.5	5.0	8.5						2,000
	6.5-6.6	LN64165P	16.5	7.0	10.5	3.0	13.0	4.2	1480	850	2,000
		LN64185P	18.5	9.0	12.5						2,000
		* LN64205P	20.5	11.0	14.0						2,000
		* LN64225P	22.5	13.0	16.0						2,000
7.8	8.0-8.3	LN78135P	13.5	4.0	7.0				2050		
		LN78165P	16.5	7.0	10.0	3.8	16.0	5.1	2200	1300	1,000
		LN78195P	19.5	10.0	13.0						
		LN78225P	22.5	13.0	16.0						

* UNDER SPECIAL REQUEST

ORNIT Blind Rivets, Kibbutz Or-Haner, M.P. Hof Ashkelon 79190, ISRAEL

Tel: +972-8661-0222, Fax: +972-8661-1380, E-Mail: info@ornit.com

www.ornit.com

